

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

PCT / SE 2004 / 0 0 1 0 1 8

REC'D 16 JUL 2004

WIPO

PCT

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande Trimble AB, Danderyd SE
Applicant (s)

(21) Patentansökningsnummer 0301830-6
Patent application number

(86) Ingivningsdatum 2003-06-23
Date of filing

Stockholm, 2004-07-07

För Patent- och registreringsverket
For the Patent- and Registration Office


Gunilla Larsson

Avgift
Fee

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

PATENT- OCH
REGISTRERINGSVERKET
SWEDEN

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 668 02 86
08-668 02 86

A SURVEYING INSTRUMENT

Technical Field of the Invention

5 The present invention relates to a surveying instrument, and to a method of operating a surveying instrument.

Description of Related Art

10 Total stations are precision survey instruments that allow a user to electronically measure the distance, as well as the vertical and horizontal angles, between the total station and any points to be surveyed. These types of measurements require a high degree of accuracy, with acceptable tolerances measured in arc-seconds for angles and millimeters for distance. The manufacture of a prior art total station therefore involves high precision trimming and adjustment of certain mechanical parts whose
15 function affects the measurements-to-be-performed.

In addition to the demand for precision, it is also important that these instruments be easy and convenient to use, because of the difficult terrain and other extreme conditions that may be present in the location where the total station is to be
20 employed. When using a prior art total station, it is necessary for the user to precisely level the instrument within a manufacturer-specified range before measurements are taken.

25 US 6,138,367 discloses a total station that includes a rotational alidade portion and an angle encoder for measuring the rotational orientation of the rotational alidade portion. The total station disclosed by US 6,138,367 further includes tilt sensors connected to a tilt predictor. The tilt predictor predicts the degree of tilt of the rotational alidade portion of a total station corresponding to the rotational orientation of the rotational alidade portion. The tilt predictor is coupled to a screen that displays
30 the measurement results to the user.

Summary

An aspect of the invention relates to the problem of further simplifying the task for the operator of a surveying instrument, while enabling reduced production costs for such a surveying instrument.

5

According to an embodiment of the invention this problem is addressed by an error compensation system for a surveying instrument comprising:

an automatic error measurement system for detecting a tilt error and an error due to mechanical imperfections in said surveying instrument;

10

a controller adapted to automatically compensate for said detected errors so as to improve an operating accuracy of said surveying instrument.

15

This solution advantageously causes a sight line of the surveying instrument to move in a vertical direction with reduced or eliminated deviation from true verticality in response to a changed vertical reference value. According to an embodiment said controller co-operates with said automatic error measurement system so as to cause a sight line of said surveying instrument to move in a vertical direction in response to manual control of a vertical direction reference value (R_v) wherein the error from true verticality is less than a predetermined amount.

20

Likewise, this solution advantageously causes the sight line to move in a horizontal direction with reduced or eliminated deviation from true horizontality in response to a manually changed horizontal reference value. According to an embodiment said controller co-operates with said automatic error measurement system to cause a point, on a sight line, at an arbitrary fixed distance from said surveying instrument to move in a horizontal direction in response to manual control of a horizontal direction reference value (R_H) wherein the error from true horizontal is less than a predetermined amount.

25

30

The magnitude of a predetermined threshold value D_F determines the vertical and/or horizontal accuracy of the aim achieved. According to an embodiment the threshold value D_F corresponds to an angle of ten arcseconds or less. According to another

embodiment the threshold value D_f corresponds to an angle of one arcsecond or less. According to a preferred embodiment the threshold value D_f corresponds to an angle of one third of an arcsecond. According to a most preferred embodiment the threshold value D_f corresponds to an angle of less than one third of an arcsecond.

- 5 This is advantageous to the user of the surveying instrument, for example when inspecting structures such as buildings, "as built". A surveying instrument equipped with the error compensation system according to the invention simplifies the task of inspecting structures by making it easier to ascertain e.g. whether a wall is truly vertical. Moreover, the error compensation system according to the invention
- 10 makes it possible for the manufacturer of the surveying instrument to allow larger mechanical imperfections in said surveying instrument without any negative consequences to the customer or user. For example, the manufacturer can allow a larger trunnion axis error in the surveying instrument. This allows for simplified production, which in turn reduces production costs. According to an embodiment of
- 15 the invention the detected errors include tilt errors as well as a trunnion axis error. The above mentioned problem is also addressed by a method of operating a surveying instrument having a movable unit that is controllably rotatable around a first axis and around a second axis, wherein said second axis may be inaccurately positioned so that it deviates from a true vertical axis, and said first axis may deviate
- 20 from being orthogonal to the second axis; the method comprising the steps of:
- a) setting a horizontal reference value R_H indicative of a desired horizontal orientation of said movable unit 20;
 - b) detecting a horizontal orientation value H_s indicative of a current rotational orientation around said second axis 90;
 - 25 c) receiving a horizontal orientation correction value H_{EC} ; DH indicative of a horizontal orientation deviation of said movable unit 20; wherein said horizontal orientation correction value H_{EC} ; DH is generated in dependence of a transverse plumb error value P_1 ; P'_1 ; said transverse plumb error value P_1 ; P' , being dependent on said horizontal orientation of said movable unit 20; and
- 30 wherein said received horizontal orientation correction value H_{EC} ; DH is dependent on the vertical orientation V of the movable unit 20 so as to compensate

for horizontal orientation deviations that may occur as a consequence of pivoting around said first axis 50;

- d) generating a horizontal position value H indicative of a current horizontal orientation of said movable unit 20 in response to said horizontal orientation value H_s and said horizontal orientation correction value H_{EC} ; DH ;
- e) generating a horizontal error value e_H in dependence on said horizontal position value (H) and said horizontal reference value R_H ;
- f) automatically controlling the horizontal orientation of the movable unit (20) in dependence of said horizontal error value e_H .

10

This solution allows for larger mechanical inaccuracy in the surveying instrument while achieving improved accuracy in the aiming of the instrument. Moreover, this solution enables an operator to aim in a desired direction with less required user interaction. For example, when an operator wishes to move the aim of the sight line from a first target in a first horizontal direction and a first vertical direction to a second target in the same horizontal direction but at a different second vertical direction; Then this method enables the operator to achieve that goal by the simple action of operating a vertical control knob only so as to change the vertical reference value. Whereas a prior art instrument, when being operated with the vertical control knob only, causes a slight shift in the horizontal aim due to inherent mechanical inaccuracies in the instrument and to leveling errors, the instrument according to an embodiment of the invention compensates for such inaccuracies.

15

20

Additionally this solution advantageously also allows for lower production costs of the surveying instrument, since the need for mechanical trimming of the instrument in connection with its production may be eliminated, or at least reduced.

25

Moreover, this solution enables manufacture of a more sturdy and stable surveying instrument, since some mechanical trimming means can be eliminated. Such mechanical trimming means are often vulnerable to mechanical shock, which may render a reduced accuracy when using a surveying instrument with such mechanical

30

08 59887300

Ink. t. Patent- och reg.verket

2003 -06- 2 3

5

Muvudföreläsningen

trimming means after having exposed it to mechanical shock e.g. by bringing it on a bumpy ride in a car.

5 Rather than mechanically trimming the surveying instrument to adjust e.g. the mutual position of the first axis and second axis in connection with manufacture, the aim of the surveying instrument according to an aspect of the invention is automatically adjusted so as to compensate for any mechanical errors. The elimination of mechanical trimming means reduces the mechanical complexity of the instrument and it eliminates or reduces the need for mechanical trimming during the
10 production of the surveying instrument. Therefore this solution allows for lower production costs. This is because the error determination mechanism is not subject to the mechanically induced errors inherent in the fundamental design of the instrument, but is totally independent. By determining the exact error as a function of the two different axes of rotation, relative to an independent reference system, and
15 automatically incorporating the corrections needed to exactly compensate for the mechanical errors, the invention produces an improved level of accuracy in the actual measurements, and true orthogonality of axis movement; this in turn produces much greater conformity to true vertical and horizontal repositioning by the user.

20

This solution makes it possible to accurately indicate a vertical line on a wall using the apparatus according to an aspect of the invention, even when the apparatus is mounted in a non-ideal position, e.g. if the apparatus is not exactly leveled.

25

A special application of this feature arises when setting out a horizontal direction that is exactly opposite to a given horizontal direction. This can traditionally be achieved by turning only the vertical motion knob to change the vertical angle approximately 180 degrees. Provided that the axes in the instrument are perfectly positioned, the new horizontal direction will be exactly opposite the reference
30 direction. If not, the horizontal aim has to be adjusted to achieve the goal.

30

Brief Description of the Drawings

For simple understanding of the present invention, it will be described by means of examples and with reference to the accompanying drawings, of which

- 5 Figure 1 is a front view of a surveying instrument according to an embodiment of the invention.

Figure 2A is a view as seen looking in the direction of arrow 130 in Figure 1, illustrating various axes in the surveying instrument.

10

Figure 2B illustrates the angular direction (H, V) of the sight line, when the surveying instrument is aimed at a target for the purpose of performing a measurement.

- 15 Figure 2C is a view as seen looking in the direction of arrow 140 in Figure 1, for illustrating the Horizontal Collimation error C_H in the surveying instrument of Figure 1.

- 20 Figure 2D illustrates the trunnion axis error T as seen in the same perspective as the observer sees Figure 1.

- 25 Figure 2E illustrates the second axis 90, a truly vertical line 155 and the trunnion axis 50 as seen in the perspective the observer sees Figure 1. An angular deviation, as illustrated in Figure 2E, between the vertical line 155 and the second axis 90 is denoted P_I .

- 30 Figure 2F illustrates the second axis 90 in a perspective perpendicular to the perspective of Figure 2E. An angular deviation, as illustrated in Figure 2F, between the vertical line 155 and the second axis 90 is denoted P_{II} .

Figure 3 shows a schematic block diagram of a first embodiment of a control system 200 for use in a surveying instrument of the type shown in Figure 1.

Figure 4 is a flow chart illustrating an embodiment of a method of operating a surveying instrument when the surveying instrument comprises a control system as described with reference to Figure 3.

5

Figure 5 shows a schematic block diagram of a second embodiment of a control system for use in a surveying instrument of the type shown in Figure 1.

Figures 6 and 7 are flow charts illustrating an embodiment of a method of operating the control system according to Figure 5.

10

Detailed Description of Embodiments

In the following description similar features in different embodiments will be indicated by the same reference numerals.

15

Figure 1 shows a front view of a surveying instrument 10 of the type commonly referred to as a total station or theodolite. An embodiment 10 of a surveying instrument according to the invention includes a movable unit 20, comprising optical equipment, as represented by a lens 30. The movable unit 20 is supported in a housing 40 in such a manner that it is pivotable relative to the housing 40 around a first axis 50, as indicated by double arrow 60. The first axis 50 may also be referred to as the trunnion axis.

20

The housing 40 comprises a lower portion 70 by means of which it is supported on a base 80 in such a manner that lower portion 70 is rotatable relative to the base 80 around a second axis 90, as indicated by double arrow 100. The housing 40 may also be referred to as the alidade portion 40.

25

Thus, by rotating the movable unit 20 around the two axes 50 and 90 the movable unit 20 can be oriented in any desired position for the purpose of carrying out an intended surveying operation.

30

For movement of the movable unit 20 around the axis 50 there is provided a drive arrangement 110 in the housing 40, and for movement of the housing 40 and the movable unit 20 around the axis 90 there is provided a similar drive arrangement 120 in the lower portion 70 of housing 40.

During operation the surveying instrument 10 may be set up so that the second axis 90 extends in a substantially vertical direction (Figure 1). For example, the surveying instrument 10 may, during operation, be supported via the base 80 on a stand 122.

Between the stand 122 and the base 80 there may be provided adjusters 124 for enabling leveling of base 80 in relation to the stand 122. The individual adjusters 124, provided between the stand 122 and the base 80, may be expandable and contractible to enable setting so that the second axis 90 extends in a substantially vertical direction (Figure 1).

Figure 2A is a view as seen looking in the direction of arrow 130 in Figure 1. Figure 2A illustrates various axes in the surveying instrument. The movable unit 20 (Figure 1) comprises optical equipment, as represented by the lens 30, and a haircross 32 (Figure 2A) defining a sight line 128. The sight line 128 may be aimed at a target for the purpose of performing a measurement. With reference to Figure 2A, the sight line 128 would, in an ideal case, always be perpendicular to trunnion axis 50.

Moreover, the trunnion axis 50 would, in an ideal case, always be perpendicular to the second axis 90.

Figure 2B illustrates the angular direction (H, V) of the sight line, when the surveying instrument 10 is aimed at a target 141 for the purpose of performing a measurement. Figure 2B illustrates a (non-realistic) ideal case, i.e. when second axis 90 is exactly vertical, the trunnion axis 50 is exactly perpendicular to axis 90, and the sight line 128 is exactly perpendicular to trunnion axis 50.

- Unfortunately, in a real case, there will always exist some mechanical imperfections. These imperfections, albeit minute, may cause the direction of the sight line 128 to deviate from the perpendicular angle in relation to trunnion axis 50. This angular deviation is herein referred to as the Horizontal Collimation error C_H . Figure 2C is an illustration the Horizontal Collimation error C_H in the surveying instrument 10.
- Figure 2C is a view as seen looking in the direction of arrow 140 in Figure 1. In other words, Figure 2C is a view as seen looking down the vertical rotation axis 90 in Fig. 1. As illustrated in Figure 2C, an axis 150 is perpendicular to the trunnion axis 50 in the Horizontal plane, and the Horizontal Collimation error C_H is the angle between axis 150 and the sight line 128. The value of the Horizontal Collimation error C_H may be adjusted by trimming the position of the haircross 32 (Fig 2A) in relation to the lens 30. Any remaining Horizontal Collimation error C_H can be compensated for in the manner described below.
- The departure from right angles between the trunnion axis 50 and the second axis 90 is herein referred to as the Trunnion axis error T. Figure 2D illustrates the Trunnion axis error T as seen in the same perspective as the observer sees Figure 1. As illustrated in Figure 2D, an axis 154 is perpendicular to the second axis 90, and the Trunnion axis error T is the angle between axis 154 and the trunnion axis 50. The value of the Trunnion axis error T may be adjusted by trimming the position of one bearing position of the Trunnion axis (Fig 1 and Fig. 2D) in relation to the second axis 90. Any remaining Trunnion axis error T can be compensated in the manner described below.
- With reference to Figure 1, the adjusters 124 should ideally be set so that axis 90 is vertical. Unfortunately, however, there will often be deviations in a real case. Figure 2E illustrates the second axis 90, a truly vertical line 155 and the trunnion axis 50 as seen in the perspective the observer sees Figure 1. An angular deviation, as illustrated in Figure 2E, between the vertical line 155 and the second axis 90 is denoted P_1 . Figure 2F illustrates the second axis 90 and the truly vertical line 155 as seen in the direction of arrow 130 in Fig 1. Hence Figure 2F illustrates the second axis 90 in a perspective perpendicular to the perspective of Figure 2E. An angular

deviation, as illustrated in Figure 2F, between the vertical line 155 and the second axis 90 is denoted P_{II} . The angular deviations P_I and P_{II} taken together are herein referred to as the total plumb error. Hence, the total plumb error may be described by the combination of two angular values P_I and P_{II} . The plumb error values P_I and P_{II} may be adjusted and reduced by means of the adjusters 124 (Figure 1).

A first embodiment of a control system

Figure 3 shows a schematic block diagram of a first embodiment of a control system 200 for use in a surveying instrument 10 of the type shown in Figure 1.

As indicated above, driver 110 is adapted to cause the movement of the movable unit 20 around the first axis 50, also referred to as the trunnion axis. The angle of deviation of the sight line from a truly vertical line is herein denoted V . Hence, activation of driver 110 is the main cause for change of the angle V .

Likewise, driver 120 causes the movement of the housing 40 around the second axis 90. The angle H is the angular deviation from a horizontal reference direction. The reference direction may, e.g. be the direction towards north. Hence, activation of driver 120 is the main cause for change of the angle H .

Control of vertical output value V

With reference to figure 3, a sensor 210 is provided for detecting the vertically angular position of the movable unit 20 relative to the alidade portion 40. The signal generated by sensor 210 is denoted V_s . The sensor 210 is connected to a controller 500 for delivering the detected signal V_s as a negative feedback in the control of driver 110. The controller 500 has an input 510 for a vertical reference signal R_v . According to one embodiment the vertical reference signal R_v is generated by user interaction, e.g. when a user turns a control knob 520. According to another embodiment the vertical reference signal value R_v is derived from co-ordinates indicating a desired orientation of movable unit 20.

08 59887300

Ink. t. Patent- och reg.verket

11

2003-06-23

Huvudfaxen Kassar

The sensor 210 is also connected to a calculation unit 220 for delivering the detected signal V_s . The calculation unit 220 is adapted to generate the vertical angle value V and the horizontal angle value H , in the manner indicated below.

5

The calculation unit 220 comprises a first calculator 230 having an input 240 for receiving the detected vertical signal V_s . The first calculator 230 also has an input 260 for receiving a signal indicative of a Vertical index V_p , and input 270 for receiving an signal indicative of a longitudinal plumb error P'_H .

10

Plumb error values P_I and P_H may be measured by means of electronic tilt sensors 222 and 224, respectively. The tilt sensors 222, 224 are typically integrated into the total station, and the data from the tilt sensors may be visually displayed to the user on a screen present on the total station. Plumb error values P_I and P_H may also be referred to as tilt error values.

15

According to one embodiment an electronic tilt sensor 222, 224 is comprised of a vial filled with fluid. The fluid in the vial is free to move, so that if the tilt sensors are not level, the level of the fluid in the vial is different from the fluid level if the tilt sensors are level. In another embodiment, an electronic tilt sensor 222, 224 includes elements suspended by wires that are used to determine the relationship between the vertical axis of the instrument and the true vertical line. The amount of tilt is measured in arc-seconds. Typical electronic tilt sensors are capable of measurements within one (1) arc-second of angle.

20

25

According to an embodiment of the invention the surveying instrument 10 includes: a housing 40, also referred to as alidade portion 40; tilt sensors 222, 224 coupled to said alidade portion, and a tilt predictor 226 adapted to predict degree of tilt of said rotational alidade portion corresponding to a rotational orientation of said rotational alidade portion. This is described in more detail in US 6,138,367, the content of which is hereby incorporated by reference. The predicted degree of tilt is defined by the combination of the two angular values P'_I and P'_H .

30

08 59887300

Ink. t. Patent- och reg.verket

2003-06-23

12

Huvudfaxen Kasse

In the embodiment shown in Figure 3, the input 270 is coupled to receive the predicted longitudinal plumb error value P'_{II} from the tilt predictor 226.

- 5 According to another embodiment a tilt sensor delivers a longitudinal plumb error value P_{II} directly on the input 270.

An advantage attained by the use of a tilt predictor is the provision of a substantially instantaneous information of the tilt status. By contrast, a tilt sensor as such is relatively slow, and the output has to stabilize before being read, wherefore the movable unit 20 would have to remain immobile for a while before the output of the tilt sensor becomes reliable.

10 According to an embodiment of the invention the first calculator 230 generates an output signal V in accordance with the following equation:

$$V = V_s + V_p + P'_{II} \quad (1)$$

wherein V_p is a vertical index value.

The value of V_p can be selected e.g. such that the output signal V is 90 degrees when the movable unit 20 is aimed such that the sight line 128 is horizontal.

20

The output signal V is delivered to device 530. The device 530 includes a memory having a first memory position 540 for a vertical start value V_A , and a second memory position 550 for storing a vertical end value. The control system 200A also includes a user input device 560. The method of operation of the control system 200A is described in detail with reference to Figure 4 below.

25

It is to be noted that the presence of a longitudinal plumb error value P'_{II} in equation (1) inherently renders the vertical orientation of the movable unit 20 dependent on its horizontal orientation, when the longitudinal plumb error value P_{II} deviates from zero. This conclusion is due to the fact that the value of the longitudinal plumb error P_{II} varies in response to rotation around the second axis 90. The solution according to an aspect of the invention compensates for this inherent drawback by providing a

30

2003-06-23

control system with a negative feedback, wherein a feedback value V is responsive to the longitudinal plumb error value P_n . As described below in connection with Figure 4, the value V can be differentiated to generate a vertical orientation correction value DV to be used in control of the vertical orientation of the movable unit 20. Thus an error in vertical orientation of the movable unit, dependent on the horizontal position of the movable unit, can be compensated. This advantageous result is clearly illustrated by the Figure 3, showing

- that the predictor 226 can calculate the longitudinal plumb error value P'_n in response to the detected horizontal position H_s ,
- that the first calculator 230 calculates the value V in response to the predicted longitudinal plumb error value P'_n ,
- that an aim corrector 665 can generate a value DV indicative of a vertical deviation, wherein the value DV depends on changes in the value V ;
- that the value DV is used as a negative feedback signal in controller 500 for adjusting the vertical aim.

Control of horizontal output value H

- With reference to figure 3, a sensor 320 is provided for detecting the horizontal angular position of the housing 40 relative to the base 80. The signal generated by sensor 320 is denoted H_s . The sensor 320 is connected to a controller 600 for delivering the detected signal H_s as a negative feedback in the control of driver 120. The controller 600 has an input 610 for a horizontal reference signal R_H . According to one embodiment the horizontal reference signal R_H is generated by user interaction, e.g. when a user turns a control knob 620. According to another embodiment the horizontal reference signal value R_H is derived from co-ordinates indicating a desired orientation of movable unit 20.
- The sensor 320 is also connected to the calculation unit 220 for delivering the detected signal H_s . The calculation unit 220 is adapted to generate horizontal angle value H , in the manner indicated below.

The calculation unit 220 comprises a second calculator 330 having an input 340 for receiving the detected horizontal signal H_s . The second calculator 330 also has an input 350 for receiving a calibration value indicative of a horizontal collimation error C_H , and an input 360 for receiving a value indicative of a preset horizontal angle H_p , and an input 370 for receiving a signal indicative of a transverse plumb error P_t . In the embodiment shown in Figure 3, the input 370 is coupled to receive a predicted transverse plumb error value P'_t from the tilt predictor 226. A tilt predictor advantageously provides substantially instantaneous information of the tilt status, as mentioned above.

According to another embodiment the transverse plumb error P_t is received directly from a tilt sensor 222.

The second calculator 330 also has an input 372 for receiving a value indicative of a trunnion axis error T . According to an embodiment of the invention the second calculator 330 generates an output signal H in accordance with the following equation:

$$H = H_s + H_p + C_H/\sin V + (T + P_t) \cdot \cot V \quad (2)$$

wherein H_p is a reference value.

The value of H_p can be defined by the user e.g. by aiming the movable unit 20 at a known reference target, and entering the horizontal angle to be displayed when the movable unit 20 is aimed towards that reference target. The user may for example aim due north, and enter "zero" as the value H to be displayed for that horizontal angular position.

The output signal H is delivered to device 630. The device 630 includes a memory having a first memory position 640 for a horizontal start value H_A , and a second memory position 650 for storing a horizontal end value H_B .

5 The devices 530 and 630 are coupled to an aim corrector 665. The aim corrector 665 is coupled to controllers 500 and 600, respectively, so as to enable adjustment of vertical and horizontal aim, respectively. The user interface 560 is also coupled to the aim corrector 665. A method of operating the surveying instrument 10 and the control system 200 is described in with reference to Figure 4 below.

According to an embodiment of the invention, the surveying instrument 10 also comprises a display 670 by means of which a user can read the measured values V and H, respectively.

10

It is to be noted that the presence of output signal value V in equation (2) illustrates that the horizontal orientation of the movable unit 20 is inherently dependent on its vertical orientation. The solution according to an aspect of the invention compensates for this inherent drawback by providing a control system with a negative feedback, wherein a feedback value H is responsive to the output signal value V. As described below in connection with Figure 4, the value H can be differentiated to generate a horizontal orientation correction value DH to be used in control of the horizontal orientation of the movable unit 20. Thus an error in horizontal orientation of the movable unit, dependent on the vertical position of the movable unit, can be compensated. This advantageous result is clearly illustrated by the Figure 3, showing

15

20

- that the second calculator 330 has an input for receiving the output signal value V.

25

- that the aim corrector 665 can generate a value DH indicative of a horizontal deviation, wherein the value DH depends on changes in the value H;

- that the value DH is used as a negative feedback signal in controller 500 for adjusting the horizontal aim.

30

A Method of Operating a Surveying Instrument

Figure 4 is a flow chart illustrating an embodiment of a method of operating a surveying instrument 10 when the surveying instrument 10 comprises a control system as described with reference to Figure 3.

- 5 An operator wishing to perform a measurement may start by setting up the stand 122 (See Fig.1) and adjusting the adjusters 124 so as to at least roughly level base 80 of the surveying instrument 10 in relation to a truly horizontal plane. The aim of this leveling may be to set the second axis 90 so that it is substantially vertical.
- 10 A set-up procedure
- The operator may perform a set-up procedure for establishing the relevant values of Horizontal Collimation error C_H and Trunnion axis error T. According to a preferred embodiment the set-up procedure also includes initiation of the tilt predictor so as to enable quick and accurate delivery of relevant predicted plumb error values P'_I and P'_II for any rotational position subsequently selected. In figure 4 a box S5 illustrates this set-up procedure.
- 15

In order to establish the error value C_H the instrument 10 is aimed at first target, and the calculation unit 220 delivers angular values V and H. These values are stored. In a subsequent step the instrument 10 is operated so as cause the driver 120 to turn the movable unit half a revolution in the horizontal sense, and so as cause the driver 110 to turn the movable unit in the vertical sense, to an aim very close to the first target. Thereafter the instrument is finely adjusted to aiming at the first target again, and reading the angular values V and H delivered by calculation unit 220. A numerical value representative of the error value C_H can be calculated in response to these measurement values. The first target should preferably be selected so that the sight line is roughly horizontal for the purpose of achieving an accurate measure of the error value C_H . The established Horizontal Collimation error C_H is stored in a memory 355.

20

25

30

A second set-up procedure, similar to the set-up procedure described above, may be used for the purpose of establishing a numerical value for the trunnion error T. This

08 59887300

Int. t. Patent- och reg.verket

2003-06-23

17

Huvudtaxen Kassen

second procedure, however, uses a target that is not close to the horizontal plane.

The established value for the trunnion error T is stored in a memory 375.

5 When the set-up procedure has been performed the calculation unit 220 of surveying instrument 10 delivers angular values V and H with an advantageously high degree of accuracy.

10 Thereafter the operator may operate the control knobs 520 and 620 so as to aim the sight line 128 onto a reference point (S10). Once the instrument is aimed at the reference point, the sensors described above will deliver relevant input signals to the calculation unit 220, resulting in a delivery of angular values V and H, respectively on the outputs of calculation unit 220.

A vertical aim lock function

15 Desiring to change the horizontal aim H by a certain angle, while intending to maintain unchanged vertical aim V, the operator may now select a function "vertical aim lock" (step S20). This function may be selected by means of a user interface 560 (Fig.3). Selection of the vertical aim lock function tells the surveying instrument 10 to make automated corrections for any deviations in vertical aim.

20

The selection of function "vertical aim lock" causes the device 530 to receive the angular values of the present aim. Hence, it may be advantageous to aim at a reference target before selection of function "vertical aim lock". Moreover, the device 530 reads the value V (See Fig 3), here denoted V_A , and stores that value in the memory location 540. Similarly, the device 630 reads the value H, here denoted H_A and stores the value H_A in the memory location 640. At this stage the operator may also be able to read the measured angular values $V=V_A$, $H=H_A$ in the display 670 (Figure 3).

25

30 In a step S30 the operator may turn the knob 620 for changing the horizontal aim by a certain angle, while intending to maintain unchanged vertical aim. Hence the

30

2003-06-23

18

Huvudfaxen Kassar

operator may turn only the control knob 620 (Figure 3) for causing the movable part 20 to rotate around the second axis 90, as indicated by double arrow 100 (Fig. 1).

When the operator has attained the desired horizontal positioning H_B of the instrument, the above mentioned mechanical imperfections may have caused a small, but measurable change in vertical aim. In other words, the operation of the "horizontal" control knob 620 may cause an unintentional or inadvertent change in vertical aim.

According to an embodiment of the invention the values V , H on the outputs of calculation unit 220 are automatically read by devices 530, 630, and these values are stored in memory locations 550 and 650, respectively. The values stored in memory locations 550 and 650 are herein referred to as V_B and H_B , respectively. Box S40 in Fig 4 illustrates this.

In a subsequent step S50, the device 530 calculates the difference DV between the values V_B and V_A , and device 630 calculates the difference DH between the values H_B and H_A .

$$DV = V_B - V_A$$

$$DH = H_B - H_A$$

20

The differential signal values DV , DH are delivered to an aim corrector 665. When the function "vertical aim lock" has been selected, the aim corrector 665 will deliver the differential signal value DV to controller 500 so as to adjust the vertical aim. The differential signal value DV is added to the vertical position control loop so that the surveying instrument 10 automatically compensates for all mechanical deviations in a servo drive fashion. Hence, when the operator has selected the function "vertical aim lock" the servo system will allow change in the horizontal aim only, and any undesired changes to the vertical aim will be automatically compensated.

25

This method simplifies the work for the operator in that the operator can take an aim at any selected reference target, and then directly achieve a vertically correct aim in another horizontal direction. Hence, according to an aspect of the invention, any

30

imperfections inherent in the mechanical construction causing a change in the vertical positioning V will be compensated. As indicated above, the compensation in the aim can be calculated in accordance with equation (1) above in conjunction with the procedure described above.

5

A horizontal aim lock function

Likewise if the procedure is made with the purpose of adjusting only the vertical aim, i.e. operating only the knob 520, this may cause a non-desired change in the horizontal aim H, due to the above mentioned mechanical imperfections. In a manner analogous to the manner described above, the operator may then select a function "horizontal aim lock" by means of the user interface. Selection of this function tells the surveying instrument 10 to make automated corrections for any deviations in horizontal aim. When the function "horizontal aim lock" has been selected, the aim corrector 665 will deliver the differential signal value DH to controller 600 so as to adjust the horizontal aim (step S70).

15

According to an embodiment of the invention the "horizontal aim lock" function comprises the steps of:

- generating a horizontal reference value R_H for indicating a selected horizontal orientation of said movable unit 20;
- activating a horizontal aim lock function of the surveying instrument (10) for maintaining said selected horizontal orientation;
- pivoting said movable unit 20 around said first axis 50 so as to change a vertical orientation of said movable unit 20;
- detecting a horizontal orientation value H, related to rotation around said second axis 90;
- receiving a horizontal error value DH indicative of a horizontal orientation deviation; said horizontal error value DH being dependent on said detected horizontal orientation value Hs;
- automatically controlling a horizontal orientation of the movable unit 20 in dependence of said horizontal reference value R_H and said horizontal error value

20

25

30

2003-06-23

20

Huvudfaxen Kossen

DH wherein said horizontal error value DH is dependent on the vertical orientation of the movable part 20.

5 The differential signal values DV, DH may be delivered to the display 670 (See Figure 3 and step S60 in Fig 4) enabling the operator to read the values DV, DH in real time, or with a predetermined delay for the purpose of enabling improved readability.

10 A Second Embodiment of a Control System

Figure 5 shows a schematic block diagram of a second embodiment 200B of a control system for use in a surveying instrument 10 of the type shown in Figure 1. The control system 200B operates to control the drive arrangements 110 and 120, respectively.

Vertical aim

20 The control system 200B according to the second embodiment includes a vertical sensor 210 delivering a detected signal V_s to an input 271 of a vertical position generator 272. The vertical position generator 272 also has an input 273 for receiving a vertical error correction value V_{ec} . The vertical position generator 272 generates an accurate vertical position value V in response to the values received on the inputs 271 and 273.

25

The output signal V is delivered to an input 274 of a first controller 280. The first controller 280 also comprises an input 290 for a reference signal value R_v which may be set by a user or operator. The reference signal value R_v is indicative of a desired value for the output value V .

30

2003-06-23

21

Huvudfaxen Kassar

An error signal e_v is generated in the first controller 280 as a difference between the reference signal value R_v and the output signal V . The error signal e_v is delivered to a regulator 300. The regulator 300 has an output 310 for a vertical control signal V_c .

- 5 The vertical control signal V_c is delivered to the drive arrangement 110 for causing an appropriate movement of the movable unit 20 around the trunnion axis 50. In this manner the control system 200B controls the vertical aim in response to the vertical reference signal value R_v , using the accurate vertical position value V generated by the vertical position generator 272.

10

The vertical error correction value V_{ec} is generated by an error correction generator 292 in dependence of the vertical index V_p and the vertical plumb error value P_{II} . According to an aspect of the invention the value V_{ec} is calculated as:

15

$$V_{ec} = V_p + P'_{II}$$

- The values of the vertical index V_p and the vertical plumb error P_{II} may be attained and delivered to the error correction generator 292 in the same manners as described above in connection with the earlier described embodiments. The value of V_p can be selected e.g. such that the output signal V is 90 degrees when the movable unit 20 is aimed such that the sight line 128 is horizontal. In a preferred embodiment the vertical plumb error value is a predicted value P'_{II} delivered by a predictor 226, as described above. A tilt predictor advantageously provides substantially instantaneous information of the tilt status, as mentioned above.

25

Horizontal aim

- A horizontal sensor 320 delivers a detected signal H_s to an input 371 of a horizontal position generator 372. The horizontal position generator 372 also has an input 373 for receiving a horizontal error correction value H_{ec} . The horizontal position generator 372 generates an accurate horizontal position value H in response to the values received on the inputs 371 and 373. Horizontal control may be achieved in

30

2003-08-23

22

Huvudfaxen Kassar

the same manner as described for vertical control above, involving: an input 374 of a controller 380 comprising an input 390 for a reference signal value R_H which may be set by a user or operator; and an error signal e_H generated dependent on a difference between the reference signal value R_H and the accurate horizontal position value H ; a regulator 400 having an output 410 for a horizontal control signal H_C for controlling a drive arrangement 120 for causing an appropriate movement of the housing 40 around the second axis 90.

In this manner the control system 200B controls the horizontal aim in response to the horizontal reference signal value R_H , using the accurate horizontal position value H generated by the horizontal position generator 372.

A horizontal correction generator 412 generates the horizontal error correction value H_{EC} . According to an aspect of the invention the value H_{EC} is calculated as:

$$H_{EC} = H_p + C_H / \sin V + (T + P') * \cot V$$

wherein H_p is a constant defining the angular position where the output signal H is zero.

The values of the horizontal index H_p , trunnion axis error T and the horizontal plumb error may be attained in the same manners as described above in connection with the earlier described embodiments. The attained values of H_p , C_H , T and P' are delivered to the error correction generator 412, which in turn operates to generate the error correction value H_{EC} in response thereof. In a preferred embodiment the horizontal plumb error value is a predicted value P' delivered by a predictor 226, as described above.

An operator may control the reference signal values R_v and R_H . According to one version of the invention the signal R_v is generated by a first control knob. Similarly the signal R_H may be generated by a second control knob.

With reference to Figure 5, control system 200B includes a positional control loop section 700. The positional control loop section 700 can operate at a high update rate to achieve fast and accurate control of the aim of the movable part 20, as described with reference to Figure 6 below.

5

The error correction values V_{EC} and H_{EC} may be generated at a lower update rate, as described with reference to Figure 7 below. Hence the error correction generators 292 and 412 may be included in an error correction section 710 of the control system 200B.

10

According to a preferred embodiment of the invention the positional control loop section 700 includes a first data processing unit, and the error correction section 710 includes a second data processing unit; wherein the first data processing unit has a higher data processing capacity than the second data processing unit. According to another embodiment the sections 700 and 710 may operate with other relations between their data processing capacities.

15

A method of operating a surveying instrument

20 Figures 6 and 7 are flow charts illustrating an embodiment of a method of operating the control system according to Figure 5.

With reference to Figure 6, an operator may perform a set-up procedure s5, as described above before starting to make measurements. The detectors 210, 320 will deliver signals V_s , H_s indicating the detected aim (step S110). The position value generators 272 and 372 will receive error correction values V_{EC} and H_{EC} , respectively, as indicated by box s120 in Figure 6. In response to the detected aim and the relevant error correction value the position value generators 272 and 372 will deliver accurate aim values V and H , respectively. The controllers 280, 380 receive reference values R_v and R_h , respectively, which may be set by a user. This is illustrated by step S130 in Figure 6.

25

30

2003-06-23

24

Huvudfoxen Kassen

As illustrated by step s140 in Figure 6, the controllers 280, 380 operate to control the aim, that is the positioning of the movable unit 20 (Figure 1), in response to the accurate aim values V and H, respectively, and the relevant reference values R_V and R_H .

5

The steps S110, S120, S130 and S140 may run in parallel for the vertical and the horizontal aim. After completion of step S140, the procedure is repeated again.

10

According to one embodiment of the invention, the method starts in response to a detected change in one of the received reference values R_H , R_V . This embodiment of a method according to the invention includes the steps of:

- a) setting a horizontal reference value R_H indicative of a desired horizontal orientation of said movable unit 20;
- b) detecting a horizontal orientation value H_s indicative of a current rotational orientation around said second axis 90;
- c) receiving a horizontal orientation correction value H_{EC} ; DH indicative of a horizontal orientation deviation of said movable unit 20; wherein said horizontal orientation correction value H_{EC} ; DH is generated in dependence of a transverse plumb error value P_i ; P'_i ; said transverse plumb error value P_i ; P'_i being dependent on said horizontal orientation of said movable unit 20; and

20

wherein said received horizontal orientation correction value H_{EC} ; DH is dependent on the vertical orientation V of the movable unit 20 so as to compensate for horizontal orientation deviations that may occur as a consequence of pivoting around said first axis 50;

25

- d) generating a horizontal position value H indicative of a current horizontal orientation of said movable unit 20 in response to said horizontal orientation value H_s and said horizontal orientation correction value H_{EC} ; DH;
- e) generating a horizontal error value e_H in dependence on said horizontal position value (H) and said horizontal reference value R_H ;
- f) automatically controlling the horizontal orientation of the movable unit (20) in dependence of said horizontal error value e_H .

30

2003 -06- 2 3

25

Huvudfaxen Kassar

According to a preferred embodiment the method further comprises:

g) repeating steps b) to f) until said horizontal error value e_H is smaller than a predetermined threshold value D_F .

- 5 The magnitude of the predetermined threshold value D_F determines the accuracy of the aim achieved. According to an embodiment the threshold value D_F corresponds to an angle of ten arcseconds or less. According to another embodiment the threshold value D_F corresponds to an angle of one arcsecond or less. According to a preferred embodiment the threshold value D_F corresponds to an angle of one third of an
- 10 arcsecond. According to a most preferred embodiment the threshold value D_F corresponds to an angle of less than one third of an arcsecond.

- In a corresponding manner a method according to the invention achieves automatic control of the vertical orientation of the movable unit in dependence on the vertical error value e_v . According to a preferred embodiment the method comprises the step
- 15 of controlling the vertical orientation of the movable unit so that error e_v is less than a predetermined predetermined threshold value D_{VF} .

- Figure 7 illustrates a method of delivery of the error correction values V_{EC} and H_{EC} , respectively. In a step S 210 error correction generator 292 receives the input values
- 20 V_F and P'_H . As mentioned above, the value of P'_H can change in dependence of the current position of the alidade portion 40, but the rate of change of the value P'_H is relatively slow.

- 25 The error correction generator 292 generates a vertical error correction value in response to the input values V_F and P'_H (Step S220), and the generated value is delivered (Step S230) to the position value generator 272.

- Steps S210, S220 and S230 may be an iterative process so that step S230 is followed
- 30 by a new execution of steps S210, S220 and S230, as indicated in Figure 7.

2003-06-23

26

Huvudfaxen Kassar

The process of generating the horizontal error correction value H_{EC} is performed in the same manner, but on the basis of the input signals T , P_i , C_H , H_P , and V .

5 The rate of change of the error correction values will, under normal operation, be much smaller than the rate of change of the detected position value V_s or H_s in response to a changed reference value R_V or R_H . It may therefore be advantageous to allocate more computer power to the execution of the method described with reference to Figure 6. The separation of the procedures for generating the error correction values V_{EC} and H_{EC} from the process of controlling the drivers 110, 120
10 advantageously makes it possible to release computer power. This is achieved by executing the procedure described with reference to Figure 7 at a lower rate, while maintaining the a highly accurate control of the positioning. In other words, this separation of procedures makes it possible to achieve an accurately updated position value and servo control of the positioning with a lower demand on the hardware.

15

According to an embodiment the control loop 700 described with reference to Figure 6 operates with a repetition frequency exceeding 100 times per second (100Hz); whereas the procedure according to Figure 7 operates with less than half of that repetition frequency. According to one version the error correction values are
20 updated at a rate of about one tenth of the repetition frequency of the control loop described with reference to Figure 6.

25

According to a preferred embodiment the control loop described with reference to Figure 6 operates with a repetition frequency exceeding 1000 times per second (1000Hz).

30

The tilt predictor 226 may be included in a third section 720, as illustrated in Figure 5. The tilt predictor 226 may operate to update predicted plumb error values P'_i and P'_H , respectively, at the same repetition frequency as error correction values H_{EC} and V_{EC} are updated.

The surveying instrument 10 (Figure 1) may include a laser adapted to send light in the direction of the sight line. When an operator changes the vertical reference value R_v , while maintaining a constant horizontal reference value, the laser light will sweep in a truly vertical fashion. The method according to embodiments of this invention will therefore enable the drawing of a very accurately vertical line on a wall, since it allows for servo control to eliminate the influence of the mechanical errors. Advantageously, the invention makes this possible even when the apparatus is mounted in a non-ideal position, c.g. even if the apparatus is positioned so that the second axis 90 deviates from the ideal, truly vertical axis.

Moreover, the surveying instrument 10 according to the invention advantageously simplifies for a user to aim in a first compass bearing and to use the surveying instrument 10 for indicating a second compass bearing exactly opposite said first compass bearing. A user may, for example first aim due North, and then achieve an aim in the true South compass bearing, by the simple action of pivoting the movable unit 20 around the first axis 50. This may be achieved by a method of operating the surveying instrument 10; the method comprising the steps of:

setting a desired first horizontal orientation of said movable unit 20 so that a horizontal component of the aim of a sight line 128 of said surveying instrument 10 is directed in a first compass bearing;

pivoting said movable unit 20 around said first axis 50 so as to change a vertical orientation of said movable unit 20 until said horizontal component of the aim of said sight line 128 of said surveying instrument 10 is directed in a second compass bearing; said second compass bearing deviating from said first compass bearing;

generating a horizontal position value H indicative of a current horizontal orientation of said movable unit 20 in response to a horizontal orientation correction value H_{EC} ; said horizontal orientation correction value H_{EC} being dependent on the vertical orientation V of the movable unit 20 so as to compensate for horizontal orientation deviations that may occur as a consequence of pivoting around said first axis 50;

automatically controlling a horizontal orientation of the movable unit 20 in dependence of said horizontal position value H so that said second compass bearing is opposite said first compass bearing.

5 According to one embodiment the above described method of operating the surveying instrument is performed in response to manual control of the direction reference value R_V and/or R_H , respectively. This is achieved e.g. when a user manually operates the vertical control knob and/or the horizontal control knob of the surveying instrument.

10

According to another embodiment the controller in the surveying instrument is adapted to automatically compensate for detected errors during remote control of said surveying instrument. In this embodiment there may be provided a receiver (not shown) coupled to deliver the reference value R_V and/or R_H to the input 290 and/or input 390, respectively, in Figure 5. A transmitter (not shown) comprising inputs for operation by a user is adapted to transmit data indicative of the reference value R_V and/or R_H to the receiver so as to cause the surveying instrument to be remotely controlled in response to the user inputs. The transmitter/receiver may communicate in a wireless manner, e.g. via a radio link, or by means of modulated light. In one version the transmitter/receiver communicates optically by means of laser light, which is modulated to carry the information about the reference value R_V and/or R_H . When a user manually operates control knobs on the transmitter for the reference value R_V and/or R_H , the transmitter operates to deliver relevant direction data to the receiver. In response to reception of the direction data the receiver may operate to deliver adequate control signals so that to the reference value R_V and/or R_H are delivered to the reference value inputs 520, 620, 290, 390. According to a preferred embodiment the control system 200A, 200B includes a servo processor coupled to communicate with the receiver and the reference value inputs 290, 390, 520, 620. The transmitter and the receiver may be embodied by transceivers for allowing bi-directional communication.

25

30

2003 -06- 2 3

Huvudfoxen Kåssan

29

In yet another version of the invention an operator may enter a certain target, in terms of co-ordinates or target reference values, via user inputs on the surveying instrument itself and in response thereto a processor in the surveying instrument will automatically calculate a corresponding direction of the sight line so as to direct the sight line towards the target. This may be achieved by entering the corresponding direction reference values into inputs 290 and 390 shown in Figure 5. In yet another embodiment of the invention the co-ordinates or target reference values are entered on user inputs at a remote location and delivered to a transmitter at the remote location for transfer to the surveying instrument by means of a transmitter/receiver assembly, thereby causing the surveying instrument to automatically direct the sight line towards a target defined by the co-ordinates or target reference values. The transmitter/receiver assembly may operate in the same manner as described above.

Claims

1. A method of operating a surveying instrument (10) having a movable unit (20) that is controllably rotatable around a first axis (50) and around a second axis (90),
5 wherein said second axis (90) may be inaccurately positioned so that it deviates from a true vertical axis, and said first axis (50) may deviate from being orthogonal to the second axis (90); the method comprising the steps of:
- a) setting a horizontal reference value (R_H) indicative of a desired horizontal orientation of said movable unit (20);
 - 10 b) detecting a horizontal orientation value (H_s) indicative of a current rotational orientation around said second axis (90);
 - c) receiving a horizontal orientation correction value (H_{EC} ; DH) indicative of a horizontal orientation deviation of said movable unit (20); wherein said horizontal orientation correction value (H_{EC} ; DH) is generated in dependence of a
15 transverse plumb error value (P_i ; P'_i); said transverse plumb error value (P_i ; P'_i) being dependent on said horizontal orientation of said movable unit (20); and
wherein said received horizontal orientation correction value (H_{EC} ; DH) is dependent on the vertical orientation (V) of the movable unit (20) so as to compensate for horizontal orientation deviations that may occur as a consequence of
20 pivoting around said first axis (50);
 - d) generating a horizontal position value (H) indicative of a current horizontal orientation of said movable unit (20) in response to said detected horizontal orientation value (H_s) and said horizontal orientation correction value (H_{EC} ; DH);
 - 25 e) generating a horizontal error value (e_H) in dependence on said horizontal position value (H) and said horizontal reference value (R_H);
 - f) automatically controlling the horizontal orientation of the movable unit (20) in dependence of said horizontal error value (e_H).

30
2. The method according to claim 1, further comprising

Ink. t. Patent- och reg.verket

2003-06-23

31

Huvudfaxen Kassa

g) repeating steps b) to f) of claim 1 until said horizontal error value (e_H) is smaller than a predetermined threshold value (D_F).

3. The method according to claim 1 or 2, wherein

5 said horizontal orientation correction value (H_{EC} ; DH) is dependent on a predicted transverse plumb error value (P'); and wherein
 the predicted transverse plumb error value (P') is generated in dependence on said detected horizontal orientation value (H_S).

10 4. The method according to claim 1, wherein

 said horizontal orientation correction value (H_{EC} ; DH) is generated in response a measured transverse plumb error value (P); said measured transverse plumb error value (P) being inherently dependent on the horizontal position of the movable unit (20) when the transverse plumb error (P) deviates from zero.

15

5. The method according to any one of claims 1, 2, 3 or 4 wherein

 steps b), d), e) and f) of claim 1 are performed with a first repetition frequency; and wherein

 said horizontal orientation correction value (H_{EC} ; DH) is updated with a
20 second repetition frequency; said second repetition frequency being lower than said first repetition frequency.

6. The method according to claim 5 when dependent on claim 2, 3 or 4, wherein

 said transverse plumb error value is updated with said second repetition
25 frequency.

7. The method according to any one of claims 2 - 6, wherein

 said predetermined threshold value (D_F) is less than ten arcseconds.

30 8. The method according to any one of claims 2 - 6, wherein

 said predetermined threshold value (D_F) is less than one arcsecond.

2003 -06- 2 3

32

Huvudfoxen Kasson

9. The method according to any one of claims 1 - 8, further comprising the step of:
pivoting said movable unit (20) around said first axis (50) so as to
change a vertical orientation of said movable unit (20).

5 10. The method according to any one of claims 1 - 9, wherein:

said vertical orientation (V) of the movable unit (20) is generated in
dependence of a longitudinal plumb error value (P_{II} ; P'_{II}); said longitudinal plumb
error value (P_{II} ; P'_{II}) being dependent on said horizontal orientation of said movable
unit (20).

10

11. A method of operating a surveying instrument (10) having a movable unit (20)
that is controllably rotatable around a first axis (50) and around a second axis (90),
wherein said second axis (90) may be inaccurately positioned so that it deviates from
a true vertical axis, and said first axis (50) may deviate from being orthogonal to the
second axis (90); the method comprising the steps of:

15

setting a desired first horizontal orientation of said movable unit (20) so
that a horizontal component of the aim of a sight line (128) of said surveying
instrument (10) is directed in a first compass bearing;

pivoting said movable unit (20) around said first axis (50) so as to
20 change a vertical orientation (V) of said movable unit (20) until said horizontal
component of the aim of said sight line (128) of said surveying instrument (10) is
directed in a second compass bearing; said second compass bearing deviating from
said first compass bearing;

generating a horizontal position value (H) indicative of a current
25 horizontal orientation of said movable unit (20) in response to a horizontal
orientation correction value (H_{EC}); said horizontal orientation correction value (H_{EC})
being dependent on the vertical orientation (V) of the movable unit (20) so as to
compensate for horizontal orientation deviations that may occur as a consequence of
pivoting around said first axis (50);

30

automatically controlling a horizontal orientation of the movable unit
(20) in dependence of said horizontal position value (H) so that said second compass
bearing is opposite said first compass bearing.

12. A method of operating a surveying instrument (10) having a movable unit (20) that is controllably rotatable around a first axis (50) and around a second axis (90), wherein said second axis (90) may be inaccurately positioned so that it deviates from a true vertical axis, and said first axis (50) may deviate from being orthogonal to the second axis (90); the method comprising the steps of:

- a) setting a vertical reference value (R_v) indicative of a desired vertical orientation of said movable unit (20);
- b) detecting a vertical orientation value (V_s) indicative of a current rotational orientation around said first axis (50);
- c) receiving a vertical orientation correction value (V_{EC} ; DV) indicative of a vertical orientation deviation of said movable unit (20); wherein said vertical orientation correction value (V_{EC} ; DV) is generated in dependence of a longitudinal plumb error value (P_n ; P'_n); said longitudinal plumb error value (P_n ; P'_n) being dependent on a horizontal orientation of said movable unit (20);
- d) generating a vertical position value (V) indicative of a current vertical orientation of said movable unit (20) in response to said detected vertical orientation value (V_s) and said vertical orientation correction value (V_{EC} ; DV);
- e) generating a vertical error value (e_v) in dependence on said vertical position value (V) and said vertical reference value (R_v);
- f) automatically controlling a vertical orientation of the movable unit (20) in dependence of said vertical error value (e_v).

13. The method according to claim 11, further comprising

- g) repeating steps b) to f) until said vertical error value (e_v) is smaller than a predetermined threshold value (D_{vt}).

14. The method according to claim 12 or 13, wherein

- said vertical orientation correction value (V_{EC} ; DV) is dependent on a predicted longitudinal plumb error value (P'_n); and wherein

the predicted longitudinal plumb error value (P'_H) is generated in dependence on a detected horizontal orientation value (H_s).

15. The method according to claim 12, wherein

5 said vertical orientation correction value (V_{EC} ; DV) is generated in response a measured longitudinal plumb error value (P_H); said measured longitudinal plumb error value (P_H) being inherently dependent on the current horizontal position of the movable unit (20).

10 16. The method according to any one of claims 12, 13, 14 or 15 wherein

steps b), d), e) and f) of claim 12 are performed with a first repetition frequency; and wherein

15 said vertical orientation correction value (V_{EC} ; DV) is updated with a second repetition frequency; said second repetition frequency being lower than said first repetition frequency.

17. The method according to claim 16 when dependent on claim 13, 14 or 15, wherein

20 said plumb error value is updated with said second repetition frequency.

18. The method according to any one of claims 13 - 17, wherein

said predetermined threshold value (D_{VF}) is less than ten arcseconds.

19. The method according to any one of claims 13 - 17, wherein

25 said predetermined threshold value (D_{VF}) is less than one arcsecond.

20. The method according to any one of claims 12 - 19, further comprising the step of:

30 pivoting said movable unit (20) around said second axis (90) so as to change a horizontal orientation of said movable unit (20).

2003-06-23

35

Huvudfaxen Kassar

21. A surveying instrument (10) having a movable unit (20) that is controllably rotatable around a first axis (50) and around a second axis (90), wherein said second axis (90) may be inaccurately positioned so that it deviates from a true vertical axis, and said first axis (50) may deviate from being orthogonal to the second axis (90);

5 the surveying instrument further comprising:

means for generating a transverse plumb error value (P_i ; P'_i); said transverse plumb error value (P_i ; P'_i) being dependent on said horizontal orientation of said movable unit (20);

10 an horizontal error corrector (412) adapted to generate a horizontal orientation correction value (H_{EC} ; DH) in dependence of a vertical position value (V) and said transverse plumb error value (P_i ; P'_i); wherein said vertical position value (V) is indicative of a vertical orientation of said movable unit (20); and

a controller (700) having:

15 a) an input (390) for receiving a horizontal reference value (R_H) indicative of a desired horizontal orientation of said movable unit (20);

b) a sensor for detecting a horizontal orientation value (H_s) indicative of a current rotational orientation around said second axis (90);

20 c) an input for receiving said horizontal orientation correction value (H_{EC} ; DH) indicative of a horizontal orientation deviation of said movable unit (20); and

25 d) a horizontal position generator (372) adapted to generate a horizontal position value (H) indicative of a current horizontal orientation of said movable unit (20) in response to said detected horizontal orientation value (H_s) and said horizontal orientation correction value (H_{EC} ; DH); and

30 e) means for generating a horizontal error value (e_H) in dependence on said horizontal position value (H) and said horizontal reference value (R_H); wherein

08 59887300

Ink. t. Patent- och reg. yrke

2003-06-23

36

Huvudfaxen Kosson

f) said controller is adapted to automatically control the horizontal orientation of the movable unit (20) in dependence of said horizontal error value (e_H).

- 5 22. The surveying instrument (10) according to claim 21, wherein
said controller is adapted to control the horizontal orientation of the movable unit (20) so that said horizontal error value (e_H) is smaller than a predetermined threshold value (D_F).
- 10 23. The surveying instrument (10) according to claim 21 or 22, wherein
said means for generating a transverse plumb error value (P_i ; P'_i) comprises a predictor adapted to generate a predicted transverse plumb error value (P'_i) in dependence on said detected horizontal orientation value (H_s).
- 15 24. The surveying instrument (10) according to claim 23, wherein
said horizontal error corrector (412) is adapted to generate said horizontal orientation correction value (H_{EC} ; DH) in dependence of said predicted transverse plumb error value (P'_i).
- 20 25. The surveying instrument (10) according to any one of claims 21, 22, 23 or 24 wherein
said controller (700) is adapted to generate an updated horizontal error value (e_H) with a first repetition frequency; and wherein
said horizontal error corrector (412) is adapted to generate an updated
25 horizontal orientation correction value (H_{EC} ; DH) with a second repetition frequency; said second repetition frequency being lower than said first repetition frequency.
26. The surveying instrument (10) according to claim 25 when dependent on claim
30 22, 23 or 24, wherein
said transverse plumb error value is updated with said second repetition frequency.

27. The surveying instrument (10) according to any one of claims 21 - 26, further comprising:

means for generating a longitudinal plumb error value (P_{II} ; P'_{II}); said
5 longitudinal plumb error value (P_{II} ; P'_{II}) being dependent on said horizontal
orientation of said movable unit (20);

a vertical error corrector (292) adapted to generate a vertical error
correction value (V_{EC}) in dependence of said longitudinal plumb error value (P_{II} ;
 P'_{II});

10 a sensor for detecting a vertical orientation value (V_s) indicative of a
current rotational orientation around said first axis (50); and

a vertical position generator (272) adapted to generate said vertical
position value (V) of the movable unit (20) in dependence of said vertical error
correction value (V_{EC}) and said detected vertical orientation value (V_s); and wherein

15 said horizontal error corrector (412) is adapted to generate said
horizontal orientation correction value (H_{EC} ; DH) in dependence of said generated
vertical position value (V) and said transverse plumb error value (P_I ; P'_I).

28. A surveying instrument (10) having a movable unit (20) that is controllably
20 rotatable around a first axis (50) and around a second axis (90), wherein said second
axis (90) may be inaccurately positioned so that it deviates from a true vertical axis,
and said first axis (50) may deviate from being orthogonal to the second axis (90);
the surveying instrument (10) comprising:

means for generating a longitudinal plumb error value (P_{II} ; P'_{II}); said
25 longitudinal plumb error value (P_{II} ; P'_{II}) being dependent on said horizontal
orientation of said movable unit (20);

a vertical error corrector (292) adapted to generate a vertical error
correction value (V_{EC}) in dependence of said longitudinal plumb error value (P_{II} ;
 P'_{II});

30 a controller (700) having:

a) an input (290) for a vertical reference value (R_v) indicative
of a desired vertical orientation of said movable unit (20);

2003-06-23

Huvudfoxen Kassar

38

- b) a sensor for detecting a vertical orientation value (V_s) indicative of a current rotational orientation around said first axis (50); and
- c) an input (273) for receiving a vertical orientation correction value (V_{EC} ; DV) indicative of a vertical orientation deviation of said movable unit (20); wherein said vertical orientation correction value (V_{EC} ; DV) is generated in dependence of a longitudinal plumb error value (P_H ; P'_H); said longitudinal plumb error value (P_H ; P'_H) being dependent on said horizontal orientation of said movable unit (20);
- d) a vertical position generator (272) adapted to generate a vertical position value (V) of the movable unit (20) in dependence of said vertical error correction value (V_{EC}) and said detected vertical orientation value (V_s);
- e) means for generating a vertical error value (e_v) in dependence on said vertical position value (V) and said vertical reference value (R_v); wherein
- f) said controller is adapted to automatically control a vertical orientation of the movable unit (20) in dependence of said vertical error value (e_v).

29. The surveying instrument (10) according to claim 28, wherein said controller is adapted to control the vertical orientation of the movable unit (20) so that said vertical error value (e_v) is smaller than a predetermined threshold value (D_{VF}).

30. The surveying instrument (10) according to claim 28 or 29, wherein said means for generating a longitudinal plumb error value (P_H ; P'_H) comprises a predictor (226) adapted to generate a predicted longitudinal plumb error value (P'_H) in dependence on said detected horizontal orientation value (H_s).

31. The surveying instrument (10) according to any of claims 21 to 30, wherein said movable unit (20) further comprises optical equipment and a hairline cross (32) defining a sight line (128) for allowing said movable unit (20) to be aimed at a target position; wherein said sight line (128) may deviate from being

orthogonal to the first axis (50); said deviation constituting a Horizontal Collimation error;

said surveying instrument (10) further comprising a memory (355) for storing an established Horizontal Collimation error value (C_H); and wherein

5 said horizontal error corrector (412) has an input coupled to receive said established Horizontal Collimation error value (C_H); said horizontal error corrector (412) being adapted to generate said horizontal orientation correction value (H_{EC} ; DH) in dependence of said established Horizontal Collimation error value (C_H) so as to obtain compensation for said Horizontal Collimation error.

10

32. An error compensation system for a surveying instrument comprising:

an automatic error measurement system for detecting a tilt error and an error due to mechanical imperfections in said surveying instrument;

15 a controller adapted to automatically compensate for said detected errors so as to improve an operating accuracy of said surveying instrument.

33. The error compensation system according to claim 32, wherein said detected errors include a trunnion error (T).

20 34. The error compensation system according to claim 32, wherein said detected errors include a horizontal collimation error (C_H).

25 35. The error compensation system according to claim 32, 33 or 34, wherein said controller co-operates with said automatic error measurement system so as to cause a sight line of said surveying instrument to move in a vertical direction in response to manual control of a vertical direction reference value (R_V) wherein the error from true verticality is less than a predetermined amount.

30 36. The error compensation system according to claim 32, 33, or 35, wherein said controller co-operates with said automatic error measurement system to cause a point, on a sight line, at an arbitrary fixed distance from said surveying instrument to move in a horizontal direction in response to manual control of a horizontal direction

2003-06-23

40

Huvudfaxen Kassar

reference value (R_H) wherein the error from true horizontal is less than a predetermined amount.

37. The error compensation system according to any of claims 32 to 36, wherein

5 said automatic error measurement system comprises a first error correction generator for generating a vertical error correction value (V_{EC}) and a second error correction generator for generating a horizontal error correction value (H_{EC}) dependent on said detected errors; and wherein

10 said controller is adapted to achieve said error compensation in dependence of said vertical and horizontal error correction values (V_{EC} , H_{EC}).

38. The error compensation system according to claim 37, wherein

15 said first error correction generator is adapted to generate the vertical error correction value (V_{EC}) in dependence on a longitudinal plumb error value (P_H ; P'_H); and

 said second error correction generator is adapted to generate the horizontal error correction value (H_{EC}) in accordance with the following equation:

$$H_{EC} = H_P + C_H/\sin V + (T + P'_H) \cdot \cot V$$

20 wherein H_P is a constant; T is a detected trunnion axis error; P'_H is a horizontal plumb error value; and V is a vertical position value dependent on said vertical error correction value (V_{EC}).

39. The error compensation system according to claim 37 or 38 when dependent on claim 37, wherein

25 said controller is adapted to generate an updated control signal with a first repetition frequency; and wherein

 said automatic error measurement system is adapted to generate said error correction values with a second repetition frequency; said second repetition frequency being lower than said first repetition frequency.

30

40. The error compensation system according to any of claims 35 or 36, wherein said predetermined amount is less than ten arcseconds.

41. The error compensation system according to any of claims 35 or 36, wherein said predetermined amount is less than one arcsecond.

5 42 The error compensation system according to any of claims 35 or 36, wherein said predetermined amount is less than one third of an arcsecond.

43. The error compensation system according to any of claims 32 to 42, wherein said controller is adapted to automatically compensate for said detected errors during
10 manual control of said surveying instrument.

44. The error compensation system according to claim 43, wherein said manual control of said surveying instrument includes manual control of a direction reference value.

15

45. The error compensation system according to any of claims 32 to 42, wherein said controller is adapted to automatically compensate for said detected errors during remote control of said surveying instrument.

20 46. The error compensation system according to any of claims 32 to 42, wherein said controller is adapted to automatically compensate for said detected errors during automatic control of said surveying instrument.

Abstract

The present invention relates to a method of operating a surveying instrument (10) having a movable unit (20) that is controllably rotatable around a first axis (50) and around a second axis (90), wherein said second axis (90) may be inaccurately positioned so that it deviates from a true vertical axis, and said first axis (50) may deviate from being orthogonal to the second axis (90); the method comprising the steps of:

- a) setting a horizontal reference value (R_H) indicative of a desired horizontal orientation of said movable unit (20);
- b) detecting a horizontal orientation value (H_s) indicative of a current rotational orientation around said second axis (90);
- c) receiving a horizontal orientation correction value (H_{EC} ; DH) indicative of a horizontal orientation deviation of said movable unit (20); wherein said horizontal orientation correction value (H_{EC} ; DH) is generated in dependence of a transverse plumb error value (P ; P'); said transverse plumb error value (P ; P') being dependent on said horizontal orientation of said movable unit (20); and wherein said received horizontal orientation correction value (H_{EC} ; DH) is dependent on the vertical orientation (V) of the movable unit (20) so as to compensate for horizontal orientation deviations that may occur as a consequence of pivoting around said first axis (50);
- d) generating a horizontal position value (H) indicative of a current horizontal orientation of said movable unit (20) in response to said detected horizontal orientation value (H_s) and said horizontal orientation correction value (H_{EC} ; DH);
- e) generating a horizontal error value (e_H) in dependence on said horizontal position value (H) and said horizontal reference value (R_H);
- f) automatically controlling the horizontal orientation of the movable unit (20) in dependence of said horizontal error value (e_H).

Ink. t. Patent- och reg.verket

2003-06-23

Huvudfoxen Kassen




Fig 1.

Ink. t. Patent- och reg.verket

71103 -06- 2 3

Huvudfaxen Kassa




Fig 2 A
Ideal core
seen in direction
of arrow 130




Fig. 2B

1st case

23/06/2003

14:50

ALBIHNS STOCKHOLM AB → 0560286
08 59887300

NR. 656

D47

Ink. t. Patent- och reg.verket

2003-06-23

Huvudfaxen Kassar




Fig. 2C

As seen in direction
of arrow 140

23/06/2003

14:50

ALBIHNS STOCKHOLM AB → 0560286

08 59887300

NR.656

D48

2

Ink. t. Patent- och reg.verket

2003 -06- 2 3

Huvudfaxen Kassa




Fig. 2D

Ink. t. Patent- och reg.verket

2003 -06- 2 3

Huvudfaxen Kassen




Fig. 2E

08010300-8

23/06/2003

14:50

ALBIHNS STOCKHOLM AB → 6560286

08 59887300

NR. 656

050

Ink. t. Patent- och reg.verket

2003 -06- 2 3

Huvudfaxen Kassen




Fig. 2F

00018300-6

Ink. t. Patent- och reg.verket

2003-06-23

Huvudfaxen Kassan




Fig. 3.

Ink. t. Patent- och reg.verket

2003-06-23

Huvudfoxen-Kassan





FIG 4

Ink. t. Patent- och reg.verket

2003-06-23

Huvudfaxen Kassa



Ink. t. Patent- och reg.verket

2003-06-23

Huvudfaxen Kassa




FIG. 6

Ink. t. Patent- och reg.verket

2003-06-23

Huvudfaxen Kassa




FIG. 7

08 59887300